

SCHEDULE J
SPECIFICATIONS –PANELS & ACCESSORIES

Shortlisted proponents will be required to provide and assemble a mockup as follows:

- Panel Mock-Up – as per description

Provide 2D and 3D layouts and parts list for Panel Mock-Up.

Proponents may be asked to provide information on all products available from the product line submitted.

FACILITIES REFERENCE CODE	DESCRIPTION	Vendor ID Code
D - Panel Mock-Up	ACOUSTIC PANELS	



NOT EXACTLY AS SHOWN

CODE NO: D - PANEL MOCK-UP

ITEM: ACOUSTICAL PANEL S

DIMENSIONS: 8' x 8' - Panel Configuration, show various height panels not to exceed 66", include options; i.e., monolithic, stack on, tackable, whiteboard, glazing, transaction top, accessibility height transaction top, name plate, coat hook, cabling management, accessory element rail, etc.

CONSTRUCTION:

- Panel thickness to be no less than 2"
- Panel skins should be replaceable without removing the panel from the panel run

- Panel system to have no creep
- Panels to have load bearing capabilities
- Glass stack on panels are available
- Fabric stack on panels are available
- Panels to include all necessary connectors at intersections, top caps and end caps where necessary
- Panel system to have a universal connector which accommodates configurations of in-line, L, T, and X.
- Optional ability to configure panels at 120°
- Panels to include optional accessory elements rail
- Panels should have the ability to vertically route data cabling
- Panels shall have ability to horizontally route cables into the base and top
- Panel should have utility poles to accommodate ceiling power and data sources
- Panels to be equipped with adjustable glides having an adjustment of not less than 1”
- Panels shall have a Noise Reduction Coefficient (NRC) of not less than 0.65 and a Sound Transmission Class (STC) of not less than 20
- Panels to have ability to connect to existing work surfaces with minimal parts and no destruction to either panel or work surface
- Transaction Tops to be high density particle board, surfaces to be high pressure laminate complete with PVC Edging, or approved equal;

FINISHES:

- Upholstery to be selected from manufacturer’s Grade 2 fabric
- Other finishes to be selected from manufacturer’s standard

EQUIVALENT TO:

- Global Evolve